

X36 HD IP IR PTZ OUTDOOR CAMERA **NEW** KAS-IRS-P3600



| Features

- **Using Ultra-Low Light sensor**

2M 1/1.9 "CMOS 이미지 센서를 사용하면 희미한 빛 환경에서도 고화질 및 깨끗한 컬러 이미지를 확인할 수 있습니다.

- **Powerful zoom capability**

36 배 광학 줌, 뛰어난 자동 초점 및 5.8 ~ 210.0 mm 초점 범위. 특히, 조리개가 F1.4 ~ F4.5이므로 다른 어떤 카메라보다 우수한 화질의 이미지를 얻을 수 있습니다.

- **Triple codec, Simultaneous multi streaming**

트리플 H/W 코덱은 서로 다른 요구 사항에 따라 서로 다른 설정으로 최대 3 개의 독립적인 스트림을 전송할 수 있습니다. 따라서 H.264 / H.265를 사용하는 완벽한 원격 비디오 모니터링 시스템을 구축할 수 있습니다.

- **Weather Proof Design**

IP66 기능을 통해 비나 눈 또는 폭풍에도 상관없이 정상적인 작동을 보장합니다.

- **불법주정차 단속 특화 모델**

X36 HD IP IR PTZ OUTDOOR CAMERA

NEW KAS-IRS-P3600

Camera

Image Device	1/1.9" Progressive Scan CMOS
Effective Pixels	Approx. 2.38 Mega pixels
Aspect Ratio	HD: 16:9 SD: 4:3
Zoom Ratio	Optical x36, Digital x12
Focal Length	f = 5.8 ~ 210mm, F1.4 ~ F4.5
Horizontal angle	72.7°(W) ~ 1.8°(T)
MIN. Illumination	COLOR : 0.05 Lux@F1.5 B/W : 0.001 Lux@F1.5, 0 Lux (IR LED On)
Day & Night	Auto(CDS/CAM) / Day / Night(ICR)
Focus	Auto/Semi Auto/Manual
DNR(2D/3D)	OFF/Level Adjustment(1~5)
Shutter Speed	1 sec ~ 1/10,000sec(60/30 mode) 1 sec ~ 1/10,000sec(50/25 mode)
AGC	Auto/Manual
White Balance	Auto/Indoor/Outdoor/Manual
WDR/BLC	OFF/BLC/WDR(Digital)
Other Function	Defog(Digital), HLC, Dynamic slow shutter

Pan/Tilt

Range	Pan: 360° (Endless) Tilt: -10° ~ 180° (Flip)
Speed	Preset: 240°/sec Manual: 0.05° ~ 180°/sec Scan: 1.4° ~ 150°/sec
Preset	255 Presets with Labels
Group	8 groups(Max. 16 presets)

General

Sensor In /Out	Built-in 1 Input / 1 Output(Relay)
Audio In / Out	1 Audio In / 1 Audio Out
Video Out	BNC: VBS 1.0 Vp-p
IR distance	More than 300M, Wave: 850nm (with adaptive synchronized with zoom ratio)
Power	AC24V 36W
Approvals*	KC, IP66, IK10
Housing	Weather proof / Vandal Proof Structure
Material	Body : Aluminum Die-casting
Dimension	Net: Ø226 x 363.3(H) mm
Weight	5Kg(approx.)
Operating Temp.	-30°C ~ 50°C

Network

Ethernet		10Base-T/100Base-Tx
Video Compression		H.265/H.264/MJPEG
Video Stream	Main	1080p/720p
	Second	D1/CIF/QCIF
	Third	1080p/720p/D1/CIF/QCIF
Stream Type		Video/Complex(Video/Audio) Stream
Frame Rate		Max. 30 /25 fps for 1080P/720P/D1/ CIF/QCIF
Bitrate		30Kbps ~ 16Mbps. Supports CBR/VBR/ FIX QP
Audio Compression		Two way, G.711 A-law, G.711 μ -law, 128kbps, sampling rate 8kHz
Local Storage		Micro SD/SDHC/SDXC card. Support up to 128GB
IVA		Motion Detection, Occlusion Detection, Line Crossing*, Region entrance/exiting*, Intrusion*, Tampering*, etc
Alarm actions		Email, Micro SD/SDCH/SDXC Record, Relay Output, Snapshot, Notification of Client
Alarm		Pre-Post Alarm
Max No. of Clients		10 users(Depending on user bandwidth)
Web Brower		IE 6.0 above
Protocols Support	IPv4	IPv4/IPv6*, TCP/IP, UDP, RTP, RTSP, RTMP, NTP, HTTP, HTTPS*, SSL*, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMP*
	DDNS	Public DDNS services Support: www.dyndns.com
	ONVIF	PROFILE S
	Security	User Authentication(ID/PW), IP Address/ Mac Address filtering*

Dimension

Unit: mm

